


Picnic Table without umbrella hole



Picnic Table with umbrella hole

Included components:
Table must be anchored.

- (4) Stainless steel drop-in anchors with $\varnothing 3/8$ -16 x 1-1/2" hex flat head stainless steel screws provided. Setting tool for 3/8"-16 drop-in anchor included.



Drop-in anchor
4X



Flat head screw
4X



Setting tool
1X

Tools Required

- Safety glasses
- Hammer drill with 1/2" diameter masonry bits
- Hammer
- 7/32 hex key/bit for installing flat head screws

ASSEMBLE WITH CARE! Pangard II® Polyester Powdercoat is a strong, long-lasting finish. To protect this finish during assembly, place unwrapped powdercoated parts on packaging foam or other non-marring surface. Do not place or slide powdercoated parts on concrete or other hard or textured surface – this will damage the finish causing rust to occur. Use touch-up paint on any gouges in the finish caused by assembly tools.




Fig. 1.4
Concrete and table leg shown
in section view for clarity

NOTE:

If specifying a Landscape Forms' umbrella, the umbrella must be ordered with the surface mount stand. The surface mount stand must be anchored. Refer to the separate installation guide for the umbrella surface mount stand for mounting instructions.

INSTALLATION:

1. Prepare proper concrete slab as required.
2. Set table in place and mark hole locations.
3. Move table and drill holes. Clear holes of debris.
4. Install drop-in anchor as shown in Fig. 1.4. Ensure top of anchor is flush or slightly below concrete surface. Expand with setting tool.
5. Set table in place and install flat head screws.
6. Tighten securely.