

LEO Area Light

Specification Sheet

| Project Name: | | | | | Job Location: | | | | |
|--|------------------------|------------------------------------|------------------------------------|----------------------------------|----------------------------------|----------------------------------|----------------------------------|--|--|
| Fixture Type: | | | | | Fixture Quantity: | | | | |
| Source LED Input Voltage 120V-277V Frequency 50/60Hz EPA 1.14 ft² Weight 40 lbs | | | | | | | | | |
| LEO is finished with Pangard II®, offered exclusively by Landscape Forms, is a 19 step program of cleaning, priming, and powdercoating that resists rusting, chipping, peeling and fading to produce the finest metal finish available for site furniture and outdoor lighting. In addition, Pangard II® contains no heavy metals and is free of Hazardous Air Pollutants. | | | | | | | | | |
| LEO Area Light | | | | | | | | | |
| | Product | LE330 (LEO 30 LED Area Light) | LE350 (LEO 50 LED Area Light) | | | | | | |
| | Distribution | T2 (Type II) | T3 (Type III) | T4 (Type IV) | | | | | |
| | Output | LO (Low Output) | HO (High Output) | | | | | | |
| | Lens | CLR (Clear Lens) | FRS (Frosted Lens) | | | | | | |
| | Color Temperate | ure 30K (3000K) | 35K (3500K) | 40K (4000K) | | | | | |
| | Input Voltage | UV1 (120V-277V, 50/60Hz) | | | | | | | |
| | Mounting | 4A (4"Ø Clamp - Single Arm) | 4B (4"Ø Clamp - Double Arm) | 5A (5"Ø Clamp - Single Arm) | 5B (5"Ø Clamp - Double Arm) | 6A (6"Ø Clamp - Single Arm) | 6B (6"Ø Clamp - Double Arm) | | |
| | Photo/Motion Sensor | NMS (No Motion Sensor) | MS1 (With Motion Sensor) | | | | | | |
| | Powdercoat Color * | | | | | | | | |
| | | | | | | | | | |

Example: LE350 - T3 - HO - CLR - 30K - UV1 - 6A - MS1 - Powdercoat Color *

^{*} Click here to view the powdercoat color options.

| LEO Aluminum Pole | | | | | | | | |
|-------------------|-------------------------|----------------------------|----------------------------|---------------|---------------|--|--|--|
| | Product | LE (LEO Area Light) | | | | | | |
| | Pole Height | 12 (144 in) | 16 (192 in) | 20 (240 in) | 25 (300 in) | | | |
| | Configuration | A (Single / Double) * | S (Staggered) ** | | | | | |
| | Twist Lock | NTW (No Twist Lock) | TW1 (With Twist Lock) | | | | | |
| | Base Option | NUT (Nut Covers) | CPT (Cover Plate) | | | | | |
| | Powdercoat Color *** | | | | | | | |

Example: $LE - 25 - S - TW1 - NUT - Powdercoat\ Color$ ***

- * Single or double luminaires available with this configuration.
 ** Available with 20 and 25 pole heights.
- *** Click here to view the powdercoat color options.

Modifications

Don't see what you are looking for? Our goal is to partner with you as the designer to manufacture solutions needed for the space you are creating. We offer the option to modify our standard product to meet certain design specifications or needs. Common modifications can include GCFI outlets, custom RAL colors, banner arm(s) mounting, and custom pole heights. Contact your local Landscape Forms representative to learn more about these offerings.



| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |

 $Please send completed forms to your Landscape Forms \ representative \ or \ contact \ us \ at \ (800) \ 430-6209 \ with \ any \ questions.$