

Lo-Glo Path Light

Specification Sheet

Project Name: _____

Job Location: _____

Fixture Type: _____

Fixture Quantity: _____

Source LED
 Input Voltage 100V-277V
 Frequency 50/60 Hz
 Weight 22 lbs

Lo-Glo is finished with Pangard II®, offered exclusively by Landscape Forms, is a 19 step program of cleaning, priming, and powdercoating that resists rusting, chipping, peeling and fading to produce the finest metal finish available for site furniture and outdoor lighting. In addition, Pangard II® contains no heavy metals and is free of Hazardous Air Pollutants.

Motive Path Light				
_____	Product	GL (Lo-Glo Path Light)		
_____	LED Count & Distribution	006L4 (6 LED, Type IV)		
_____	Drive Current	035F (Standard Output)		
_____	Color Temperature	27K (2700K)	30K (3000K)	35K (3500K) 40K (4000K)
_____	Input Voltage	UV1 (100V-277V, 50/60 Hz)		
_____	Mounting	SM (Surface Mount)	PA (Paver Adapter)	
_____	Powdercoat Color **			

Example: GL – 006L4 – 035F – 40K – UV1 – SM – Powdercoat Color **

** Click here to view the powdercoat color options.

Modifications

Don't see what you are looking for? Our goal is to partner with you as the designer to manufacture solutions needed for the space you are creating. We offer the option to modify our standard product to meet certain design specifications or needs. Common modifications can include GCFI outlets, custom RAL colors, banner arm(s) mounting, and custom pole heights. Contact your local Landscape Forms representative to learn more about these offerings.

Notes

Please send completed forms to your Landscape Forms representative or contact us at (800) 430-6209 with any questions.