landscapeforms

Specification Sheet | DW100



Housing & Materials

Cast and extruded aluminum construction, welded ground and finished for seamless transition. Factory sealed and replaceable machined aluminum LED cartridge with UV stable, impact resistant diffused acrylic lens. All hardware is magni-coated for optimum corrosion and 'antiseize' protection.

Electrical

Surge protected 120V - 277V 50/60Hz electronic driver located inside the pole. Non-dimming as standard, 0-10V dimming available upon request. -40°C start temperature.


Light Engine

Outline features a replaceable LED cartridge with die-cast aluminum heatsink, high power LEDs on a RoHS compliant circuit board, and secondary optics. All cofigurations are available in 2700K, 3000K, 3500K, and 4000K. >80CRI across all available color temperatures. Luminiares meet or exceed TM21 L70: >60,000 hrs

Mounting

Outline bollard is mounted at grade using galvanized steel anchor bolts. Template and anchoring hardware included.

Distributions



Outline reinterprets the familiar light column, communicating refinement and elegance with the robustness required for public space environments. A performance luminaire, a wayfinding element and an architectural detail, Outline is equally at home in the streetscape or on campus, throughout parks and public plazas, beautifully defining space through form and light.

Outline includes luminaires at 10', 12', and 4' heights, each with a selection of distribution options and lumen packages. At the pathlight scale, Outline's 4' illuminated bollard utilizes a directed optic designed to maximize on-center spacing and uniformity. The bollard is also offered in an unlit version to provide further options in space delineation.

Outline is Buy America Compliant and International Dark-Sky Approved.

Warranty

LED lighting products are warranted for six years.

Certification

UL Listed for Wet Location, International Dark Sky Approved, RoHS Compliant, Buy America Compliant



Designed by Landscape Forms

Click here for patent information related to this product.

Specification Sheet | DW100

Specification

Luminaire

Product

Product	Color Temperature	Distribution	Powdercoat	
DW101 (Unlit Bollard)				
DW102 (Lit Bollard)	27K (2700K) 30K (3000K) 35K (3500K) 40K (4000K)	T3 (Type III) T5 (Type V)	See powdercoat color options on the Material / Colors Sheet.	

Example: DW102 - 27K - T3 - MBK

Modifications


Modifications listed are the most common changes/additions requested. If your requirements aren't shown here, select 'other' and write in the modification needed. Please provide as much detail as possible to streamline the quoting process. All modifications to standard products will require evaluation and quoting approved by Landscape Forms prior to order placement.

Part Number	Modification	Description
CPC	Custom Powdercoat Color	
CLC	Colored LED or Turtle Safe	
	Other	




Specification Sheet | DW100

DW101 Luminaire Dimensions and weight



Weight: 28 lbs

DW102 Luminaire Dimensions and weight



Weight: 28 lbs

Specification Sheet | DW100

Luminaire Performance Data (3000K)


Height	Distribution Type	Lumens	Efficacy (Im/W)	BUG Rating	Watts
4'	Type III	679	49	B0-U0-G1	14
	Туре V	1023	49	B1-U0-G1	21


Lumen output scaling factors: 2700K (0.947), 3500K (1.046), 4000K (1.053)

4' Lit Bollard

Visual comfort light engine @ 3000K







1.0fc 0.5fc 0.2fc

Material / Colors Sheet | DW100



Architectural Series - Powdercoated Metal* (Fine Texture)

Neutral Series - Powdercoated Metal*



Vivid Series - Powdercoated Metal* (Fine Texture)



Specification Sheet | DW100

Powdercoated Metal

Powdercoated Metal Pangard II[®] Polyester Powdercoat is a hard, yet flexible, finish that resists rusting, chipping, peeling and fading. In addition to colors shown, a wide selection of optional and custom colors may be specified for an upcharge.

* All colors and patterns shown are approximate and may vary from sample and final.

Visit landscapeforms.com for more information. Specifications are subject to change without notice. ©2024 Landscape Forms, Inc. Printed in U.S.A.

landscapeforms.com | specify@landscapeforms.com