

# Tumbler

## Specification Sheet

Project Name: \_\_\_\_\_ Job Location: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_ Fixture Quantity: \_\_\_\_\_

**Source** LED  
**Input Voltage** 120V-277V  
**Frequency** 50/60 Hz  
**EPA** 0.84 ft<sup>2</sup>  
**Weight** 14.5 lbs (luminaire only)

The Tumbler luminaire is aluminum extrusion with a natural aluminum powdercoat finish offered Urbidemis with a clear or opal / diffused tempered glass.

Pole & Wall Mount Luminaire							
_____	<b>Product</b>	TML					
_____	<b>LED Configuration</b>	16	24	C ( CoB ) *			
_____	<b>Drive Current</b>	A ( 350 mA )	B ( 500 mA )				
_____	<b>Color Temperature</b>	1 ( 3000K )	2 ( 4000K )				
_____	<b>Distribution</b>	WF ( Wide Flood )	F ( Flood )	M ( Medium )	S ( Spot Flood )	TII ( Type II )	TIII ( Type III ) TIV ( Type IV )
_____	<b>Lens</b>	Null ( Clear )	O ( Opal / Diffused )				
_____	<b>Color</b>	AS ( Aluminum Silver )	BK ( Black )				


\* CoB provides a Wide Flood distribution only.

EXAMPLE: TML - 16 - B - 1 - WF - O - AS

Catenary Luminaire				
_____	<b>Product</b>	TML		
_____	<b>LED Configuration</b>	16	24	C ( CoB ) *
_____	<b>Drive Current</b>	A ( 350 mA )	B ( 500 mA )	
_____	<b>Color Temperature</b>	1 ( 3000K )	2 ( 4000K )	
_____	<b>Distribution</b>	WF ( Wide Flood ) *	TII-II ( Quad Oval )	TV ( Type V )
_____	<b>Lens</b>	Null ( Clear )	O ( Opal / Diffused )	
_____	<b>Bracket</b>	C ( Catenary )		
_____	<b>Color</b>	AS ( Aluminum Silver )	BK ( Black )	

\* CoB provides a Wide Flood distribution only.

EXAMPLE: TML - 16 - B - 1 - TV - O - C - BK




Catenary


Mounting Accessories				
_____	<b>Product</b>	TML		
_____	<b>Bracket</b>	01 ( Single Column )	02 ( Wall )	03 ( Catenary ) *      04 ( Double Column )
_____	<b>Color</b>	AS ( Aluminum Silver )	BK ( Black )	

\* Automatically selected when the catenary luminaire is selected.


EXAMPLE: TML – 01 – BK



Single Column



Wall



Double Column

Tumbler Aluminum Pole Height	Pole #	Mounting	Diameter	Wall	Weight
3.4m ( 11.2 ft )	TMF11P	( 1 ) Single Column Bracket	Straight 4.5"	0.125"	29 lbs
	TMF11P	( 1 ) Double Column Bracket	Straight 4.5"	0.125"	29 lbs
4.2m ( 13.8 ft )	TMF21P	( 1 ) Single Column Bracket	Straight 4.5"	0.125"	33 lbs
	TMF22P	( 2 ) Single Column Brackets, Staggered Heights, 180° Orientation	Straight 4.5"	0.125"	33 lbs
	TMF21P	( 1 ) Double Column Bracket	Straight 4.5"	0.125"	33 lbs
5.0m ( 16.4 ft )	TMF31P	( 1 ) Single Column Bracket	Straight 4.5"	0.125"	38 lbs
	TMF32P	( 2 ) Single Column Brackets, Staggered Heights, 180° Orientation	Straight 4.5"	0.125"	38 lbs
	TMF31P	( 1 ) Double Column Bracket	Straight 4.5"	0.125"	38 lbs
6.6m ( 21.7 ft )	TMF41P	( 3 ) Single Column Brackets, Spiral Configuration, 120° Orientation	Stepped 6"/4.5"	0.188"	80 lbs

\* Landscape Forms can provide poles for your catenary project. Contact the factory for more information.

Pole Options							
_____	<b>Twist Lock</b>	Null ( None )	T ( Twist Lock Receptacle )				
_____	<b>Color</b>	BLK ( Black )	DSK ( Dusk )	MBK ( Matte Black )	MER ( Mercury ) *	SIL ( Silver )	SCL ( Storm Cloud )      TNM ( Titanium )

\* Mercury from Landscape Forms is our recommended color match for aluminum silver from Urbidermis.

EXAMPLE: TMF41P – T – MER

**Modifications**

Don't see what you are looking for? Our goal is to partner with you as the designer to manufacture solutions needed for the space you are creating. We offer the option to modify our standard product to meet certain design specifications or needs. Common modifications can include GCFI outlets, custom RAL colors, banner arm(s) mounting, and custom pole heights. Contact your local Landscape Forms representative to learn more about these offerings.

**Notes**

---



---



---



---

Please send completed forms to your Landscape Forms representative or contact us at (800) 430-6209 with any questions.